


STAINLESS STEEL THREAD END FITTINGS SERIES

不锈钢丝扣管件系列

◆ 特点:


连接形式: 螺纹、软管、堵头
材质为: SUS304、SUS316制成
管道流量控制: DN8~100及1/4"~4"
适用于各种条件及连接需要

内接头 Hexagon Nipple




SIZE	DN	L	D
1/4	8	34	15×6
3/8	10	37	18×6
1/2	15	40	22×6
3/4	20	44	28×6
1	25	48	35×6
1-1/4	32	52	44×8
1-1/2	40	55	49×8
2	50	58	61×8
2-1/2	65	63	77×10
3	80	66	90×10
4	100	69	115×10

外接头 Socket Banded




SIZE	DN	L	D
1/4	8	28	22
3/8	10	30	25
1/2	15	34	28
3/4	20	39	34
1	25	42	41
1-1/4	32	49	50
1-1/2	40	53	56
2	50	60	69
2-1/2	65	66	88
3	80	69	102
4	100	72	127

45° 弯头 45° Elbow




SIZE	DN	ΦA	L
1/4	8	21.0	18.0
3/8	10	25.0	20.0
1/2	15	29.5	22.0
3/4	20	35.6	25.0
1	25	43.0	28.0
1-1/4	32	52.4	33.0
1-1/2	40	58.0	36.0
2	50	72.0	43.0
2-1/2	65	87.0	50.0
3	80	100.32	55.0
4	100	125.5	64.0

90° 弯头 90° Elbow



SIZE	DN	L	D
1/4	8	22	22
3/8	10	23	25
1/2	15	27	28
3/4	20	30	34
1	25	35	41
1-1/4	32	42	50
1-1/2	40	46	56
2	50	53	69
2-1/2	65	62	88
3	80	69	102
4	100	83	128

异径弯头 Reducer Elbow



SIZE	L	L1	D	D1
1/2 3/4	45	41	35	29
3/4 1	52	47	41	34
1/2 1 1/4	52	42	41	29
1/2 1 1/4	64	49	51	35
3/4 1 1/2	70	57	57	42
1 2				
3/4 2	84	69	70	51
1 2				
1 3/4 2	84	75	70	57
1 1/2 2				

STAINLESS STEEL THREAD END FITTINGS SERIES

不锈钢丝扣管件系列


◆ 特点:

连接形式: 螺纹、软管、堵头
材质为: SUS304、SUS316制成
管道流量控制: DN8~100及1/4"~4"
适用于各种条件及连接需要

◆ Feature


Type:Screwed、hose、plug
Material quality:SUS304、SUS316
Flux domination of pipeline:
DN8~100&1/4"~4"
Applicable to various conditions and connected to

三通 Tee




SIZE	DN	L	D
1/4	8	22	22
3/8	10	23	25
1/2	15	27	28
3/4	20	30	34
1	25	35	41
1-1/4	32	42	50
1-1/2	40	46	56
2	50	53	69
2-1/2	65	62	88
3	80	69	102
4	100	83	128

异径三通 Reducer Tee




SIZE	DN	L	L1	D	D1
1/2	3/4	51	45	35	29
1/2	1	53	50	42	29
3/4	1	58	52	42	35
3/4	1 1/4	63	61	51	35
1	1 1/4	68	63	51	42
1-1/2	1 1/2	71	70	57	42
3/4	1 1/2	71	70	57	42
1	2	80	70	57	51
3/4	2	80	70	57	51
1	2	85	83	70	51
1 1/4	2	85	83	70	51
1 1/2	2	90	83	70	57

四通 Cross




SIZE	DN	L	D
1/2	15	50	30
3/4	20	56	35
1	25	66	42
1-1/4	32	80	52
1-1/2	40	87	58
2	50	102	70

内外弯头 Inside & outside socket elbow



SIZE	DN	L	L1	Dd
1/2	15	53	35	30
3/4	20	60	42	35
1	25	69	50	42

六角接头 Hex.plug(HP)



SIZE	H	L
1/8	11	12
1/4	15	14.5
3/8	18	16
1/2	22	19.5
3/4	28	21
1	35	24
1-1/4	43.5	27
1-1/2	49.5	27
2	62	32
2-1/2	77.5	34
3	90.5	37.5
4	117	44

STAINLESS STEEL THREAD END FITTINGS SERIES

不锈钢丝扣管件系列


◆ 特点:

连接形式: 螺纹、软管、堵头
材质为: SUS304、SUS316制成
管道流量控制: DN8~100及1/4"~4"
适用于各种条件及连接需要

◆ Feature


Type:Screwed、hose、plug
Material quality:SUS304、SUS316
Flux domination of pipeline:
DN8~100&1/4"~4"
Applicable to various conditions and connected to

活接头 Conical Union




SIZE	DN	L	L1	S	S1
1/4	8	38	15	33×8	18×8
3/8	10	39	16	36×8	22×8
1/2	15	43	17	38×8	26×8
3/4	20	45	19	46×8	32×8
1	25	53	20	55×8	39×8
1-1/4	32	55	22	65×8	48×8
1-1/2	40	59	24	74×8	54×8
2	50	64	25	88×8	66×8
2-1/2	65	68	27	104×10	83×10
3	80	70	28	120×10	96×10
4	100	78	30	148×10	125×10

内外螺纹活接头 Union(M/F)




SIZE	DN	L	SW
1/4	8	50	30
3/8	10	50	35
1/2	15	57	42
3/4	20	67	47
1	25	68.3	53
1-1/4	32	83	71
1-1/2	40	86.3	78
2	50	94	92
2-1/2	65	113.3	112
3	80	127	126
4	100	154.3	157

异型外接 Reducing Socket Banded



SIZE	L	D	D1
1/2 3/4	35	35	29
1/2 1	38	42	29
3/4 1	39	42	34
1/2 1 1/4	44	51	34
3/4 1 1/4	44	51	42
1 1 1/2	48	57	41
3/4 1 1/2	48	57	41
1 2	53	69	51
3/4 2	53	69	51
1 2	53	69	57
1/2 2	53	69	57

抛管子内丝 Coupling



SIZE	D(Φ)	L
1/8	15	18
1/4	18	18
3/8	22	22
1/2	26	25
3/4	33.7	30
1	40	35
1 1/4	48	40
1 1/2	55	40
2	69	45
2 1/2	85	50
3	100	50
4	127	50

STAINLESS STEEL THREAD END FITTINGS SERIES

不锈钢丝扣管件系列


◆ 特点:

连接形式: 螺纹、软管、堵头
材质为: SUS304、SUS316制成
管道流量控制: DN8~100及1/4"~4"
适用于各种条件及连接需要

◆ Feature


Type:Screwed、hose、plug
Material quality:SUS304、SUS316
Flux domination of pipeline:
DN8~100&1/4"~4"
Applicable to various conditions and connected to

抛光管子单头丝 Half-nipple




SIZE	A	B	C
1/2	18	21.3	25
3/4	20	26.9	30
1	20	33.7	35
1 1/4	20	42.4	40
1 1/2	20	48.3	40
2	22	60.3	43
2 1/2	22	76.1	45
3	25	88.9	45

抛光管子双头丝 Barrel Nipple




SIZE	S	L	A
1/4	2.0	40	
3/8	2.0	40	10
1/2	2.5	60	13
3/4	2.5	60	15
1	3.2	60	18
1 1/4	3.2	80	21
1 1/2	3.2	80	
2	3.6	100	24
2 1/2	3.6	100	
3	4.0	120	
4	4.5	120	

抛光管子全丝 Nipple



SIZE	SIZE	L	D
1/2	15	50	30
3/4	20	56	35
1	25	66	42
1-1/4	32	80	52
1-1/2	40	87	58
2	50	102	70

补芯 Bushing



SIZE	DN	L	H
1/4	8	15	19
3/8	10	20	20
1/2	15	24	23
3/4	20	30	25
1	25	35	30
1-1/4	32	45	30
1-1/2	40	50	33
2	50	63	37
2-1/2	65	78	46
3	80	92	48
4	100	118	51

STAINLESS STEEL THREAD END FITTINGS SERIES

不锈钢丝扣管件系列


◆ 特点:

连接形式: 螺纹、软管、堵头
材质为: SUS304、SUS316制成
管道流量控制: DN8~100及1/4"~4"
适用于各种条件及连接需要

◆ Feature


Type:Screwed、hose、plug
Material quality:SUS304、SUS316
Flux domination of pipeline:
DN8~100&1/4"~4"
Applicable to various conditions and connected to

抛光皮管外牙 Hose Nipple





SIZE	DN	L	D
1/2	15	50	30
3/4	20	56	35
1	25	66	42
1-1/4	32	80	52
1-1/2	40	87	58
2	50	102	70

水管接头 Hexagon Hose Nipple




SIZE	DN	ΦD	L	SW
1/4	8	6.35	47.0	16.5
3/8	10	9.50	55.0	20.0
1/2	15	12.70	64.0	23.5
3/4	20	19.05	68.0	31.0
1	25	25.40	71.0	38.5
1-1/4	32	31.80	80.0	46.0
1-1/2	40	38.10	95.0	52.0
2	50	50.80	105.0	62.0
2-1/2	65	63.50	107.0	80.0
3	80	76.20	112.0	91.0
4	100	101.60	130.0	116.5

堵头 Plug



SIZE	DN	L	B
1/2	15	50	30
3/4	20	56	35
1	25	66	42
1-1/4	32	80	52
1-1/2	40	87	58
2	50	102	70

管盖 Cap



SIZE	Φ1	L
1/8	13.7	13.5
1/4	16.7	17
3/8	20.7	17.5
1/2	25.2	21
3/4	30.7	22.5
1	38.2	26
1-1/4	47.5	29
1-1/2	54	29
2	66.5	33.5
2-1/2	83.5	38.5
3	97	42
4	123	48.5